



## Media Processors Simplify Multi-Projection Workflows for Immersive Experiences

### ET-FMP50

Media Processors Simplify Multi-Projection Workflows for Immersive Experiences

#### Key Features

---

Flexible Design Streamlines Installation

---

Simple Yet High-Precision Adjustment

---

Smooth and Continuous Content Playback



ET-FMP50

<https://eu.connect.panasonic.com/gb/en/projectors/et-fmp50>

<b>Type</b>	Box-type
<b>Terminals -&gt; HDMI™ OUT</b>	HDMI™ x 4, Audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz)
<b>Terminals -&gt; AUDIO OUT(M3 Stereo Mini Jack)</b>	3.5 mm stereo mini-jack
<b>Terminals -&gt; LAN</b>	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T, NDI@ compatible
<b>Terminals -&gt; USB TYPE A</b>	USB 3.0 (Type A) x 2
<b>Video format</b>	HAP <sup>*1</sup> / H.264, 8-bit, 3840 x 2160 pixels, 60p, YP<sub>B</sub>P<sub>R</sub></sub> 4:2:0, 300 Mbps / H.265, 8-bit, 4096 x 4096 pixels, 60p, YP<sub>B</sub>P<sub>R</sub></sub> 4:2:0, 300 Mbps
<b>Max. video output resolution</b>	3840 x 2160/60p x 1 or 1920 x 1080/60p x 4 <sup>*2</sup>
<b>Audio format</b>	AAC-LC, 16-bit, stereo
<b>Storage</b>	4 TB
<b>Operating system</b>	Linux
<b>Power supply</b>	AC 100–240 V, 50/60 Hz
<b>Maximum power consumption</b>	59 W (TBD)
<b>Dimensions (W x H x D) -&gt; Width (not including protruding parts)</b>	210 mm (8 1/4") (TBD)
<b>Dimensions -&gt; Height (not including protruding parts)</b>	44 mm (1 23/32") (TBD)
<b>Dimensions -&gt; Depth (not including protruding parts)</b>	295 mm (11 5/8") (TBD)
<b>Weight</b>	Approx. 2.0 kg (4.41 lbs) (Excluding AC adapter and cord) (TBD)
<b>ENVIRONMENT -&gt; Operating Environment(Temperature)</b>	0–40 °C (32–104 °F)
<b>ENVIRONMENT -&gt; Operating Environment(Humidity) (No condensation)</b>	10–80 % (no condensation)
<b>Footnote Description</b>	1. ET-FMP50 only. Available from CY2024 Q4. 2. When four HDMI™ outputs are used simultaneously.