



65-inch Class 4K entry-level display that flexibly matches corporate meeting rooms and educational use.

TH-65CQE2

The Panasonic Connect TH-65CQE2 4K Professional display is designed for 24-hours/day continuous operation and crystal-clear viewing clarity. The display provides a brightness of 500cd/m² with an anti-glare panel, and minimum haze treatment, reducing the reflection of ambient light and vastly improving visibility. For ultimate flexibility and a clean look without set-top-boxes or cables, the TH-65CQE2 is also equipped with a built-

Key Features

High image quality

Reliability and ease of installation

System scalability



TH-65CQE2

<https://eu.connect.panasonic.com/gb/en/professional-displays/cqe2-series/th-65cqe2>

| | |
|--|---|
| DISPLAY PANEL -> Screen Size | 65-inch class (64.52-inch / 1638.9 mm) |
| DISPLAY PANEL -> Brightness (typ.) | 500cd/m ² |
| DISPLAY PANEL -> Aspect ratio | 16:9 |
| DISPLAY PANEL -> Effective Display Area (W x H) | 1428.4 x 803.5 mm (56.23" x 31.63") |
| DISPLAY PANEL -> Resolution | 3840 x 2160 |
| DISPLAY PANEL -> Contrast Ratio (typ.) | 1200:1 |
| DISPLAY PANEL -> Dynamic Contrast Ratio | 50000:1 |
| DISPLAY PANEL -> Response Time (typ.) | 8.0 ms (G to G) |
| DISPLAY PANEL -> Viewing Angle(H / V) | 178 ° / 178 ° (CR>10) |
| DISPLAY PANEL -> Panel Surface Treatment | Anti-glare type |
| DISPLAY PANEL -> Haze | 0.01 |
| CONNECTION TERMINAL -> HDMI™ IN | HDMI™ Type A Connector x 4 (HDCP 2.2) |
| CONNECTION TERMINAL -> SERIAL IN | Stereo mini jack (φ 3.5 mm) x 1, RS-232C Compatible |
| CONNECTION TERMINAL -> IR IN | Stereo mini jack (φ 3.5 mm) x 1 |
| CONNECTION TERMINAL -> AUDIO OUT (L / R) | Stereo mini jack (φ 3.5 mm) x 1 SPDIF x 1 |
| CONNECTION TERMINAL -> LAN | RJ45 x 1 Compatible with PLink™ 10BASE-T/100BASE-TX |
| CONNECTION TERMINAL -> USB TYPE A | USB connector Type A x 1 : DC 5 V / Max 0.9 A, (USB 3.0 is supported) USB connector Type A x 1 : DC 5 V / Max 0.5 A, (USB 2.0 is supported) USB connector Type A x 1 : DC 5 V / Max 0.5 A, (USB 2.0 is supported) (Internal) |
| CONNECTION TERMINAL -> USB TYPE C | USB connector TYPE C x 1 : DC 5 V / Max 3.0 A, (USB 3.0 is supported, DP Alt Mode) |
| CONNECTION TERMINAL -> microSD | microSD / SDHC / SDXC / Max 1TB |
| CONNECTION TERMINAL -> Wi-Fi | Yes (Dongle) |
| CONNECTION TERMINAL -> Bluetooth® | Bluetooth® 5.1, HID / A2DP |
| CONNECTION TERMINAL -> RF In (ANTENNA / CABLE) | F Connector x 1 |
| Compatible OS and browsers -> browser | HTML5 (Vwed) |
| Compatible OS and browsers -> Android™ OS | ● |
| AUDIO -> Built in Speaker | 20 W [10 W + 10 W] |
| ELECTRICAL -> Power Supply | AC220-240 V 50 Hz / 60 Hz 1.4 A(U): AC 110-127 V 50 Hz/60 Hz 2.6 A |
| ELECTRICAL -> Power Consumption | 160 W (Shipping Condition) |
| ELECTRICAL -> On Mode Average Power Consumption | 160 W (Picture Mode: [Natural]) |
| ELECTRICAL -> Power Off Condition | 0 W |
| ELECTRICAL -> Stand-by Condition | 0.5 W |
| ELECTRICAL -> Apparent power | 262 VA |
| ELECTRICAL -> Energy efficiency class for Europe | G class |
| MECHANICAL -> Dimension(W) | 1456 mm (57.32") |
| MECHANICAL -> Dimension(H) | 853 mm (33.58"), 835 mm (32.84") |
| MECHANICAL -> Dimension(D) | 96 mm (3.78") |
| MECHANICAL -> Weight | Approx. 24.6 kg (54.3 lbs) |
| MECHANICAL -> Bezel Width(T) | 12.9 mm (0.51") |
| MECHANICAL -> Bezel Width(B) | 16.1 mm (0.63") |
| MECHANICAL -> Bezel Width(L) | 12.9 mm (0.51") |
| MECHANICAL -> Bezel Width(R) | 12.9 mm (0.51") |
| MECHANICAL -> Pitch for Wall-Hanging / Screw / Screw hole depth | VESA Compliant 600 x 400 mm (23.7" x 15.8") / M6 / 10 mm (0.39"), Allowable screw length 24 mm (0.95") |
| INSTALLATION -> Orientation | Landscape / Portrait (clockwise rotation) |
| INSTALLATION -> Tilting Angle | Landscape installed 20 degrees forward |
| INSTALLATION -> Operating Time *2 | 16 h/day |
| ENVIRONMENT -> Operating Environment(Temperature) | 0 °C to 40 °C (32 °F to 104 °F) 0 °C to 35 °C (32 °F to 95 °F) |
| ENVIRONMENTAL -> Operating Environment(Humidity) (No condensation) | 20% to 80% |
| Footnote Description | 1. : Excluding remote IR sensor 2. : Including remote IR sensor 3. : Based on IEC 62087 Ed.2 measurement method 4. : Displaying a still image for a long time may cause burn-in (image persistence artifacts), it could be mitigated when display video image. 5. : Please contact your sales representative with regard to the tilt angle before installation. |