ROJECTION


VIDEO MOTORE PROJECTION SCREENS

with electrical command, varnished aluminium case

Professional screens with electrical control, realised with box in aluminium varnished with white epoxy powders which can be easily mounted to the wall or to the ceiling, through a pair of suspension brackets freely positioned on the length of the box. Upon request, the screen can be provided with radio remote control and a pair of special brackets to space the screen up to 22 cm from the wall. The screens are made with (standard) fire-proof, washable, professional white fabric, and upon request, with other fabrics for front and rear projections in order to satisfy all particular projection needs. Functioning is quick and silent thanks to the construction quality and materials used. Particularly suitable for home theatre and video-projections in medium-size board rooms, university rooms, training centres, management offices, hotels and holiday camps.

Technical Features

- Realised with the following projection fabrics: SOFT WHITE, SOFT MATT WHITE, SOFT WHITE TRANSOUND, RETRO (see technical data sheet at pages 1-2-3)
- In the standard version, the screen is lowered from the front side of the box, in case of wall installation it lowers at aprox. 81,5-97,5 mm wall distance; on demand, the screen can be supplied with rear lowering system, in this case the wall distance will be aprox. 22,5-16,5 mm. On screen size 350x300 and 400x300 the fabric lowers very close to the wall.
- Extruded aluminium case, epoxy powder coated, in white RAL 9010 colour, section 85x93mm, with rounded corners; provided with reinforcement on the upper side to hold wall fixing clamps; on the lower side a longitudinal slot with rounded edges allows the descend of the projection.
- Internal silver anodized aluminium tube for fabric wind up Ø 60 mm, which includes a reliable electric motor mounted on special rubber silent blocks.
- Powerful electric motor, single phase, IMQ trade-mark, CE, 5-year guarantee from purchasing date, power supply 200V-50Hz, absorption 0,5A, protection IP 44, 17 RPM., on the standard version the motor is mounted on the left hand side, on demand it can be mounted on the right hand side.
- Screen up and down electric inverter, standard supplied
- Screen up and down limit switches factory adjusted, possibility of different settings if necessary. The screen can also be stopped at intermediate height by pressing the electric inverter switch
- Suspension brackets are standard supplied and can be mounted anywhere along the whole housing length. Brackets are steel made, epoxy powder coated in white RAL 9010 colour, they are suitable both for wall or ceiling installation thanks specific expansion anchors.
- Robust individual packing in double cardboard type volcano
- Product CE certified, 12 month warranty to the conditions indicated on the manual
- Accessories on demand: radio remote control, spacing brackets
- Case overall dimensions: screen base size + 12 cm; case overall dimensions
 including mounting brackets: screen base size + 20 cm





I III									
SOFT WHITE	SOFT MATT WHITE	TRANSOUND	RETRO			1		1	
052601	052643	052621	052639	VIDEO MOTORE 150x150	150x150	157x159,3	166x14x14	8	10
052801	052843	052821	052839	VIDEO MOTORE 180x180	180x180	187x189,3	200x14x14	11	13
053201	053243	053221	053239	VIDEO MOTORE 200x200	200x200	207x209,3	216x14x14	12	14
057401	057443	057421	057439	VIDEO MOTORE 200x250	200x250	207x259,3	216x14x14	12	14
057501	057543	057521	057539	VIDEO MOTORE 200x300	200x300	207x309,3	216x14x14	12	14
053801	053843	053821	053839	VIDEO MOTORE 250x200	250x200	257x209,3	266x14x14	15	17
054001	054043	054021	054039	VIDEO MOTORE 250x250	250x250	257x259,3	266x14x14	16	18
054101	054143	054121	054139	VIDEO MOTORE 250x300	250x300	257x309,3	266x14x14	16	18
057601	057643	057621	057639	VIDEO MOTORE 300x225	300x225	307x234,3	316x14x14	17	20
057701	057743	057721	057739	VIDEO MOTORE 300x250	300x250	307x259,3	316x14x14	19	22
057801	057843	057821	057839	VIDEO MOTORE 300x300	300x300	307x309,3	316x14x14	19	22
ACCESSORIES AND SPARE PARTS									
090015	COMANDO RADIO HOME (ricevitore + trasmettitore) portata ml 60						25x21x17	0,5	0,6
090001	COPPIA STAFFE DISTANZIATRICI da cm 25 (discesa telo a cm 22 dalla parete)						25x21x17	0,5	1,0
090006	INVERTITORE a posizioni fisse con tasto stop, montaggio a sbalzo							0,9	1,0
090007	COPPIA STAFFE DI SOSPENSIONE (oltre a quella già in dotazione)						25x21x17	0,2	0,3

Size, in cm, weights expressed in kilograms, diagonal expressed in inches (")

1 Rat

Legenda

Code

- Screen size (AxB)
- Viewing size / inches (A'xB'/O")
- Viewing size (A'xB')
- Total screen size (WxH)
- Total size closed
- Min-max total size
- Screen case size
- Counterweight size

Top extra drop

- Max extra top drop
- Lumen
- kg Max load
- → Distance
- **↔** Distance
- Rur
 - Fixing
- ↑ Arn
 - +
- ----
- loints



Cable management



Volume



Projector case



rucking



Net weight



Gross weight